

Eaton JM60060-3MW14

Catalog Number: JM60060-3MW14

Eaton Bussmann series JM modular fuse block, Multi-Wire load-side lug, 60 A, 3P, 120°C, 50 lb-inches max, Class J, CVR(I)-J-60060, Black, Box lug, 200 kAIC, 75 °C, Stranded, Panel/DIN rail, 600 V

General specifications

Product Name	Catalog Number
Eaton Bussmann series JM modular fuse block	JM60060-3MW14
	UPC
	051712620642
Product Length/Depth	Product Height
3.7 in	2.6 in
Product Width	Product Weight
4.5 in	0.7125 lb
Warranty	Compliances
Not Applicable	RoHS Compliant
Certifications	
ARO	
European Pressure Equipment Directive (PED) 97 /23 EC	



Electrical rating

Amperage Rating

60 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

600 V

Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class J

Number of Poles

Three-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

General information

Accessories

CVR(I)-J-60060

Connection

Box lug

Mounting method

Panel

DIN rail

Special features

Multi-Wire Load-Side Lug

Resources

Catalogs

JM60060-3MW14-FUSE BLK, J 600V 60A 3P

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - JM60060-3MW14



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)