



**SKU:** CSWD-10-14-58

**UPC:** 0783669691818

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 10, 2 Holes, 1/4in Bolt Size, 5/8in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                          |                |
|--------------------------|----------------|
| Barrel Marking           | Ink            |
| Barrel Type              | Standard       |
| Connecting Angle         | 180°           |
| Connection               | Compression    |
| Contains DE-OX®          | No             |
| Flared End               | No             |
| ILSCOs Die Index Number  | NA             |
| Mounting Hole Type       | Thru           |
| Narrow Tang              | No             |
| Number of Mounting Holes | 2              |
| Sight Window             | Yes            |
| Slotted                  | No             |
| Tang End Shape           | Slightly Round |
| Undrilled                | No             |

### Dimensions

|                             |         |
|-----------------------------|---------|
| Barrel Length (IN)          | 0.39    |
| Barrel Length (mm)          | 9.906   |
| Dimension G (IN)            | 0.29    |
| Dimension G (mm)            | 7.366   |
| Height (IN)                 | 0.261   |
| Height BX (IN)              | 2.25    |
| Height (mm)                 | 6.6294  |
| Inside Diameter (IN)        | 0.149   |
| Inside Diameter (mm)        | 3.7846  |
| Length (IN)                 | 1.76    |
| Length (mm)                 | 44.704  |
| Mounting Hole Diameter (IN) | 0.281   |
| Mounting Hole Diameter (mm) | 7.1374  |
| Mounting Hole Spacing (IN)  | 0.63    |
| Mounting Hole Spacing (mm)  | 16.002  |
| Outside Diameter (IN)       | 0.237   |
| Outside Diameter (mm)       | 6.0198  |
| Strip Length (mm)           | 11.4935 |
| Tang Length (IN)            | 1.25    |
| Tang Length (mm)            | 31.75   |
| Tang Thickness (IN)         | 0.06    |
| Tang Thickness (mm)         | 1.524   |
| Tang Width (IN)             | 0.42    |

|                 |                    |
|-----------------|--------------------|
| Tang Width (mm) | 10.668             |
| Weight (LB)     | 0.0113886000662372 |
| Weight BX (LB)  | 0.86               |
| Width (IN)      | 0.42               |
| Width BX (IN)   | 5                  |
| Width (mm)      | 10.668             |

### Conductor Ranges

|                                                        |                                  |
|--------------------------------------------------------|----------------------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA                               |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol                           |
| Conductor Range CU Stranded (Primary, run, main, line) | 10 Str                           |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                               |
| Expanded Conductor Range                               | 10 Str - 14 Str /10 Sol - 12 Sol |
| Flex Conductor Range                                   | NA                               |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Insulation         | NA     |
| Material           | Copper |

### Additional Technical Specifications

|                |       |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial               | Yes             |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366969181     |

### Bolt and Screw Sizes

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 1/4 |
|-------------------------|-----|

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| NEBS Rating              | Level 3                                                                                                             |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|            |        |
|------------|--------|
| Color      | Silver |
| Color Code | NA     |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|