

Catalog No. 2TLA050011R1132

Description: "MKEY8, SOL NPT, 24V STD. KEY"

UPC No 804325609241

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and head, spring lock (power to unlock), 2000N holding force. 24VDC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with standard key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Туре	Safety Lock

Specifications		
Product Class	Safety Locks & Process Locks	
Product Main Type	MKey	
Supply Voltage	24VDC	
Outputs	Contact	
Number of Outputs	4NC + 2NO	
Degree of Protection	IP67	

Classifications	
ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions	
Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Width	46 mm
Product Net Weight	0.78kg

Safety Information	
Performance Level	Up to e



Created on: 11/16/2023

electrification.us.abb.com Created on: 11/16/2023