

Product data sheet

Characteristics

QOBXD350

Mini circuit breaker, QO, 50A, 3 pole, 240/415 VAC, 3 kA, bolt on mount



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	50 A
Voltage Rating	240/415 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	Not rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	Icu 3 kA 240/415 V AC 50/60 Hz IEC 947-2 Ics 10 kA
Number of Panel Spaces	3
Tightening Torque	44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) AWG 8...AWG 2)
Height	3.13 in (79.50 mm)
Depth	2.91 in (73.91 mm)
Width	2.23 in (56.64 mm)

Environment

Certifications	IEC
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00920 - QO INTERNATIONAL SENA
Discount Schedule	DE2A
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	3.40 in (8.636 cm)
Package 1 width	2.30 in (5.842 cm)
Package 1 Length	4.00 in (10.160 cm)

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------