



Main

Range of Product	Lexium Cobot
Product or Component Type	Robot controller
Product Compatibility	5 kg payload robot cobot 7 kg payload robot cobot
Discrete input number	16
Discrete output number	16
Analogue input number	2
Analogue output number	2

Complementary

Input voltage	100...240 V AC 50/60 Hz
I/O rated voltage	24 V DC
Communication interface	TCP/IP Modbus TCP Modbus RTU Profinet Ethernet/IP
IP Degree of Protection	IP44
Material	Stainless steel
Width	16.14 in (410 mm)
Height	12.09 in (307 mm)
Depth	9.25 in (235 mm)
Net Weight	26.46 lb(US) (12 kg)
Standards	GB 11291.1:2011 EN/ISO 10218-1:2011 EN 60204-1:2018 EN/ISO 12100:2010 EN/ISO 13849-1:2015 EN 61000-6-2:2005 EN 61000-6-4:2007+A1:2011 ISO 13849-1:2015 ISO 13849-2:2012 ISO 14644-1 ISO 9001:2015 UL 1740 ANSI/RIA R15.06 CAN/CSA Z434 NFPA 79 CAN/CSA C22.2 No. 24 REACH RoHS
Marking	CE KC TÜV

Ordering and shipping details

GTIN	3606486845509
------	---------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.80 in (32.500 cm)
Package 1 Width	15.75 in (40.000 cm)
Package 1 Length	23.62 in (60.000 cm)
Package 1 Weight	39.58 lb(US) (17.952 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	37.40 in (95.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	175.49 lb(US) (79.600 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------