Rittal - The System.

Faster – better – everywhere.





KX 1301.000 E-box KX

State: 2/6/2025 (Source: rittal.com/us-en)



KX 1301.000 - E-box KX Stainless steel

The E-Box KX, stainless steel offers remarkable ease of assembly and flexibility when selecting lock systems. The standard 180° hinges provide easy access to the enclosure interior.







Features

Model No.	KX 1301.000	
Product description	The small enclosure KX, E-Box KX, stainless steel offers rema ease of assembly and flexibility when selecting lock systems. standard 180° hinges provide easy access to the enclosure in	
Material	Housing: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Carbon steel Stainless steel 1.4404 (AISI 316L)	
Surface finish	Housing and cover: Brushed, grain 180 Mounting panel: Zinc-plated	
Supply includes	Mounting panel Cam lock with 3 mm double-bit insert	
Protection category IP to EN 60 529	IP 66	
Type rating according to UL 50E	Type 1 Type 3R Type 3RX Type 4 Type 4X Type 12	

© Rittal 2025

Features

Dimensions	Width: 200 mm
	Height: 300 mm
	Depth: 155 mm
	Width: 7.87 "
	Height: 11.8 ″
	Depth: 6.1 "
Dimensions of mounting plate (W	175 mm x 275 mm
x H)	6.89 ″ x 10.8 ″
Material thickness - enclosure	1.25 mm
	0.05 ″
Material thickness - door	1.25 mm
	0.05 ″
Lock	No. of locks: 1
Base material	Stainless steel 1.4404 (AISI 316L)
Packaging unit	1 pc(s).
Net weight	3.88
Gross weight	3.889
Customs tariff number	94032080
EAN	4028177919037
E-Number Sweden	E3465169
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas	
	DNV-GL	
	Lloyds Register of Shipping	
	UL + C-UL (listed)	

© Rittal 2025 3

Approvals

Explanations

Declaration of conformity

Declaration of conformity UK

© Rittal 2025