Rittal - The System.

Faster – better – everywhere.





CS 9828.500 CS Toptec

State: 2/8/2025 (Source: rittal.com/us-en)



CS 9828.500 - CS Toptec

Outdoor enclosure with 100 mm transport base/plinth and rain canopy with projections on all sides. Side panels, rear panel and door fully double-walled on the outside, the entire TS8 frame is available for interior installation.

Features

Model No.	CS 9828.500		
Version	Without cutout		
Product description	Outdoor enclosure with 100 mm transport base/plinth and rain canopy with projections on all sides. Side panels, rear panel and door fully double-walled on the outside, the entire TS8 frame is available for interior installation.		
Material	Housing frame: Stainless steel 1.4301 (AISI 304) Enclosure panels and base/plinth panels: Aluminum, AIMg3 Rain canopy: Aluminum		
Surface finish	Powder-coated UV-resistant pure polyester		
Color	RAL 7035		
Supply includes	Double-walled outdoor housing, fully preconfigured Enclosure frame with 25 mm system perforation in roof and base frames as well as vertical profiles with 2 mounting levels Front door with door stay, swing lever handle and semi-cylinder, lock BJ20027 Side panels left and right Rear panel Rain canopy Base/plinth with screw-fastened flange plates and screw-fastened trim panels front and rear		
Dimensions	Width: 800 mm Height: 1,200 mm Depth: 800 mm Width: 31.5 " Height: 47.2 " Depth: 31.5 "		

© Rittal 2025

Features

Protection category IP to IEC 60 529	IP 55	
IK code	IK10	
Note	All enclosure panels are double wall and grounded (external wall to internal wall) CS Toptec is the foundation for project solutions in the outdoor sector. It can be requested under these order numbers: For individual installations: 9774.099, for baying: 9774.005	
Base material	se material Aluminum	
Packaging unit 1 pc(s).		
Net weight 96		
Gross weight 98		
EAN 4028177962743		
ETIM 9 EC000261		
ECLASS 8.0 27180101		

Approvals

Explanations	Declaration of conformity
	200141141101110111011111111

© Rittal 2025 3