## Rittal – The System.

Faster – better – everywhere.





# VX 5863.600 VX SE Floormount Enclosure

State: 2/8/2025 (Source: rittal.com/us-en)



### VX 5863.600 - VX SE Floormount Enclosure NEMA 12/3R

Free-standing/ Floormount sheet steel enclosure with stable enclosure body, two integral mounting levels, internally fastened rear panel and door. Roof and sides from a single piece with roll-formed frame and solid bottom.

#### **Features**

Model No.	VX 5863.600
Product description	Free-standing/ Floormount sheet steel enclosure with stable enclosure body, two integral mounting levels, internally fastened rear panel and door. Roof and sides from a single piece with roll-
	formed frame and solid bottom. Enclosure widths from 1200 to
	1800 mm and enclosure depths from 300 to 500 mm. Includes full
	width drip shield for added protection and removable bottom plugs
	for easy installation of accessory leg kits.
Material	Housing: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
	Base plates: Carbon steel, 1.5 mm
	Mounting panel: Carbon steel, 3.0 mm
Surface finish	Housing, door and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting panel: Zinc-plated
Color	RAL 7035
Supply includes	Housing, solid top and sides
	Door(s)
	Right-hand door catch on single-door enclosures may be swapped
	to the left
	Mounting panel
	Base plate with removable floorstand kit plugs
	Rear panel, internally fastened
	Lock: 3 mm double-bit
	2 punched rails, 18 x 39 mm

© Rittal 2025 2

### **Features**

Dimensions	Width: 1,600 mm  Height: 1,600 mm  Depth: 400 mm  Width: 63 "  Height: 63 "  Depth: 15.7 "
Dimensions of mounting plate (W x H)	1,496 mm x 1,499 mm 58.9 " x 59 "
Installation depth	356 mm 14 ″
Protection category IP to EN 60 529	IP 55
Protection category NEMA	NEMA 12
Type rating according to UL 50E	Type 1 Type 2 Type 3 Type 3R Type 12
IK code	IK10
Packaging unit	1 pc(s).
UPC-Code	93695

© Rittal 2025 3