


# Rittal – The System.

Faster – better – everywhere.



## CX 6721.000

## CX Console Top-Section

State: 2/8/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CX 6721.000 - CX Console Top-Section

Four widths offer the best conditions for individual monitoring and a three-part construction of the CX desk system.



## Features

|                     |                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Model No.           | CX 6721.000                                                                                                                  |
| Version             | Top piece                                                                                                                    |
| Product description | Four widths offer the best conditions for individual monitoring and a three-part construction of the CX desk system.         |
| Material            | Housing: Carbon steel, 1.5 mm<br>Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal                                     |
| Surface finish      | Housing and door: Dipcoat primed, powder-coated on the outside, textured paint                                               |
| Color               | RAL 7035                                                                                                                     |
| Supply includes     | Housing<br>Cover hinged at bottom, including cover retainer<br>Open base for individual cable entry<br>Lock: 3 mm double-bit |
| Dimensions          | Width: 800 mm<br>Height: 515 mm<br>Width: 31.5 "<br>Height: 20.3 "                                                           |
| Top depth           | 125 mm<br>4.92 "                                                                                                             |
| Bottom depth        | 245 mm<br>9.65 "                                                                                                             |

# Features

|                                     |                                                                                                                                                              |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IK code                             | IK10                                                                                                                                                         |
| Note                                | For a 3-piece console setup, a desk unit and pedestal are required                                                                                           |
| Protection category IP to IEC 60529 | IP 55                                                                                                                                                        |
| Base material                       | Carbon steel                                                                                                                                                 |
| Dimensions                          | Width: 800 mm<br>Height: 515 mm<br>Top depth: 125 mm<br>Bottom depth: 245 mm<br>Width: 31.5 "<br>Height: 20.3 "<br>Top depth: 4.92 "<br>Bottom depth: 9.65 " |
| No. of locks                        | 2                                                                                                                                                            |
| Lock version                        | Cam                                                                                                                                                          |
| Lock Insert                         | 3 mm double-bit                                                                                                                                              |
| Lock                                | Lock version: Cam<br>No. of locks: 2<br>Lock Insert: 3 mm double-bit                                                                                         |
| Packaging unit                      | 1 pc(s).                                                                                                                                                     |
| Net weight                          | 18                                                                                                                                                           |
| Gross weight                        | 20.5                                                                                                                                                         |
| Customs tariff number               | 94032080                                                                                                                                                     |
| EAN                                 | 4028177983670                                                                                                                                                |
| ETIM 9                              | EC000784                                                                                                                                                     |
| ETIM 8                              | EC000784                                                                                                                                                     |
| ECLASS 8.0                          | 27180504                                                                                                                                                     |

## Approvals

# Approvals

|              |                           |
|--------------|---------------------------|
| Approvals    | UL + C-UL (listed)        |
| Explanations | Declaration of conformity |