


# Rittal – The System.

Faster – better – everywhere.



## SV 9343.230

## NH fuse-switch disconnect, size 00 to 3

State: 2/8/2025 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9343.230 - NH fuse-switch disconnecter, size 00 to 3

## With electronic fuse monitoring

### Features

|                                               |                                                                                                                          |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Model No.                                     | SV 9343.230                                                                                                              |
| Material                                      | Polyamide<br>Fire behavior corresponding to UL 94<br>Contact tracks: Electrolytic copper, silver-plated                  |
| Color                                         | Chassis: RAL 7035<br>Cover: RAL 7035/7001                                                                                |
| Clamping area for laminated copper bars:      | Clamping area width: 50 mm<br>Clamping area height: 10 mm<br>Clamping area width: 1.97 "<br>Clamping area height: 0.39 " |
| For bar systems with center-to-center spacing | 60 mm                                                                                                                    |
| Cable outlet                                  | Top/bottom                                                                                                               |
| Type of connection (electrical)               | Screw M10                                                                                                                |
| Rated operating current max.                  | 400 A                                                                                                                    |
| Rated operating voltage                       | 400 V - 690 V, 3~                                                                                                        |
| For NH size                                   | 2                                                                                                                        |
| Test specification                            | IEC 60 947-3<br>IEC 60 269-2 (fuse inserts)                                                                              |
| Dimensions                                    | Width: 210 mm<br>Height: 298 mm<br>Width: 8.27 "<br>Height: 11.7 "                                                       |
| Connection for round conductor cross-sections | 10 - 240 mm <sup>2</sup>                                                                                                 |

# Features

|                              |                                         |
|------------------------------|-----------------------------------------|
| Suitable for busbars         | Height: 5, 10 mm<br>Height: 0.2, 0.39 " |
| Number of poles              | 3-pole                                  |
| Packaging unit               | 1 pc(s).                                |
| Net weight                   | 3.2                                     |
| Gross weight                 | 3.52                                    |
| Copper weight (kg per piece) | 1                                       |
| Customs tariff number        | 85369095                                |
| EAN                          | 4028177540415                           |
| ETIM 9                       | EC001040                                |
| ECLASS 8.0                   | 27371401                                |

# Approvals

|              |                                                           |
|--------------|-----------------------------------------------------------|
| Approvals    | CQC-CCC                                                   |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |