

Straight Blade Devices, Connector, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Black and White

By Hubbell Wiring Device-Kellems Catalog # HBL5369CST

Straight Blade Devices, Connector, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Black and White

Features

- Spring termination for a faster and more secure terminal connection
- · Ribbed housing is impact and chemical resistant
- Superior cord grip design protects terminations from excess strain
- · Accepts #14 #10AWG, solid or stranded

General

Performance

Color Black and White Cord Range 0.230"-0.720"(5.8-18.3) Contact Manufacturer **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Horsepower - Maximum Insulation Insulated Body Item Type Insulgrip® Connector Material Nylon Material - Mounting Hardware Cord Mounted 2-Pole Number Of Poles Operating Temperature Maximum continuous 75°C and minimum -40°C without Impact

Dimensions

Display Size Standard Sized Product
Weight 0.2 lb

Electrical Ratings

Connectivity Spring Termination

Current / Amperage Rating 20 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase

Voltage Rating 125 V

Conductor Related

Conductor Range #14 AWG to #10 AWG
Cord Type All Listed Portables
Number Of Conductors 3-Wire Grounding
Number Of Wires 3-Wire
Wire Size #14 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)

• CSA Certified to C22.2 No. 42 File 280

Fed. Spec. W-C596G
NEMA* WD-6 Compliant
UL Listed to UL498 File E1706

Nema Rating 5-20P

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Sales Drawings - M14757 Warranty - Industrial & Commercial Products

Related Products

HBL5366CST - Straight Blade Devices, Plug, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V. 5-20P. Black and White

Voltage - Withstands 2,000V minimum

> Environmental -Flammability - UL 94 V-2

Electrical - Current

• Electrical - Dielectric

rated current

Interrupting - Certified for

current interrupting at full

 Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)

 Mechanical - Product Identification - Ratings are a permanent part of the device

 Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Series Insulgrip®

Size 3.28 in x 1.41 in x 1.09 in

Style Standard

Temperature Rating Maximum continuous 75°C;

minimum -40°C (w/o impact)

Type Connectors UPC 783585965383



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK-HBL5369CST-SPEC-EN | REV 1/2024