Hubbell-PRO

60/63 A, 380-415 VAC, 3-POLE, 4-WIRE

Watertight Receptacle

HUBBELL

Features

- · IP67 environmental ratings
- Impact and corrosion resistant insulated non-metallic housing
- Sequential contact engagement to prevent a momentary over-voltage
- Color coded housings provide quick identification of mating devices

Ordering Information

Heavy Duty Products, IEC Pin

and Sleeve

UPC **Catalog Number** 783585675718 C460R6WA

Description

Color

Listings

All constructions are UL Listed & cUL Listed FileE14632 UL1686 Standard for Pin & Sleeve Configurations VDE, CE


Specifications

Application **High Ampacity Connections** Connection Pressure Screw Terminal Wire Size #6AWG to #4AWG

PBT Material

Screw Mount Mounting





Complementary Products

Complementary Products

Adapter Plate, Back Box

Performance

Electrical

Dielectric Voltage Withstand 3000V AC 600V AC RMS Max. Working Voltage

Mechanical

Impact Resistance Per CSA C22.2 No. 182.1 / UL1682

Product Identification Identification and ratings are marked on device

housing

Terminal Identification Terminals identified in accordance with North

American and IEC conventions

Environmental

HB Flammability Ingress Protection IP67 Moisture Resistance IEC 60309-1

Temperature Rating Maximum Continuous: 75° C; Minimum

Continuous: -40° C w/o impact, -25° with impact.

Online Resources

Customer Sales Drawings

eCatalog

Installation Instructions

