

Eaton 170M1360

Catalog Number: 170M1360

Fuse-link, high speed, 20 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1360
	Model Code
	FUSE 20A 690V 000/80 GR UC
UPC	EAN
051712216616	5027590440806
Product Length/Depth	Product Height
105 mm	46 mm
Product Width	Product Weight
300 mm	145.1 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	



Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

76.7 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

20 A

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other

Fuse size

000

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Top fuse status indicator

Construction size

000

Clearing (I²T)

78 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M8

Utilization category

gR (general purpose semiconductor protection)

Resources

Catalogs

170M1360-FUSE 20A 690V 000/80 GR UC

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M size 000 10A to 315A

UKCA 170M size 000 10A to 315A

Specifications and datasheets

Eaton Specification Sheet - 170M1360

Watt losses

7 W

Type

Fuse

Fuse shape

Square body, slotted offset bolted tags

Breaking capacity

200 kA

Class

Class gR

Pre arc (I2T)

11.5

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia