

Eaton 170M3265

Catalog Number: 170M3265

Fuse-link, high speed, 200 A, AC 690 V, compact DIN 1, 45 x 58 x 134 mm, aR, DIN, IEC, type K indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3265
	Model Code
	FUSE 200A 690V 1*KN/110 AR UC
UPC	EAN
051712255493	5027590446716
Product Length/Depth	Product Height
305 mm	65 mm
Product Width	Product Weight
145 mm	340.5 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	



Product specifications

Interrupt rating

200 kAIC

Clearing loss

35

Center-to-center distance of connections

106 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

DIN 43 620

Amperage Rating

200 A

Fuse type

Bolted tag

DIN 43653

Fuse system (according to IEC 60269)

Other

Fuse size

1*

Voltage rating

690 V

Fuse indicator

Centre fuse status indicator

Construction size

Other

Clearing (I2T)

15000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M3265--Eaton Bussmann series high speed square body fuse

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Technical data sheets

720014 DIN 43653 690V

Mounting dimension

M10

Utilization category

aR (accompanied semiconductor protection)

Watt losses

35 W

Type

Fuse

Fuse shape

Square body, slotted center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I²T)

2200

Application

semiconductor protection

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)