

Eaton 170M6009

Catalog Number: 170M6009

Fuse-link, high speed, 550 A, AC 690 V, DIN 3, 76 x 76 x 109 mm, aR, DIN, IEC, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6009
	Model Code
	FUSE 550A 690V 3/80 AR UC
UPC	EAN
051712262545	5996516017241
Product Length/Depth	Product Height
168 mm	76 mm
Product Width	Product Weight
95 mm	892 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	



Product specifications

Interrupt rating

200 kAIC

Clearing loss

100

Center-to-center distance of connections

78 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

550 A

Fuse type

DIN 43653

/80 Visual indicator

Bolted tag

Fuse system (according to IEC 60269)

Other

Fuse size

3

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Top fuse status indicator

Construction size

3

Clearing (I²T)

135000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M10

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M6009-Eaton Bussmann series high speed square body fuse

Specifications and datasheets

Eaton Specification Sheet - 170M6009

Technical data sheets

720014 DIN 43653 690V

Utilization category

aR (accompanied semiconductor protection)

Watt losses

100 W

Type

Fuse

Fuse shape

Square body, slotted center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

19500

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)