

Eaton 170M6260

Catalog Number: 170M6260

Fuse-link, high speed, 630 A, AC 690 V, DIN 3, 76 x 92 x 139 mm, aR, DIN, IEC, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6260
	UPC
	051712263610
EAN	Product Length/Depth
5996516018682	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Warranty
940 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

Product specifications

Interrupt rating

200 kAIC

Clearing loss

105

Center-to-center distance of connections

108 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

630 A

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Fuse system (according to IEC 60269)

Other

Fuse size

3

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Centre fuse status indicator

Construction size

3

Clearing (I²T)

210000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M10

Resources

Catalogs

170M6260–Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Technical data sheets

720014 DIN 43653 690V

Utilization category

aR (accompanied semiconductor protection)

Watt losses

105 W

Type

Fuse

Fuse shape

Square body, slotted center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

69500

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)