

Eaton 170M6762

Catalog Number: 170M6762

Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6762
	UPC
	051712812320
EAN	Product Length/Depth
5996516020685	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Warranty
986 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

114 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

800 A

Fuse type

US Style

FKE/115 Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other

Fitted with:

Type K Indicator for micro

Fuse size

3

Voltage rating

690 V

Fuse indicator

Centre fuse status indicator

Construction size

3

Clearing (I2T)

465000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

Other

Resources

Catalogs

170M6762-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - 170M6762

Utilization category

aR (accompanied semiconductor protection)

Watt losses

115 W

Type

Fuse

Fuse shape

Square body, center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

69500

Application

semiconductor protection

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)