



ARCA IEC / ARCA 404021 / ARCA 404021 NO MP

ARCA 404021 NO MP 8120009N

Dimensions 400 x 400 x 210.

Including: Cabinet base. door with PUR gasket. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

- **PC:** IP66; IK10; EN 62208:2011. IEC 62208:2011,EN 61439-1:2011. IEC 61439-1:2011,EN 61439-4:2013. IEC 61439-4:2012

Product number: 8120009N

[DOWNLOAD PRODUCT CARD](#)

Technical data

Product:

Product nr: 8120009N

Description: Cabinet. PC

Remarks: Grey cover. 2-point locking.

Package: 1

Unit: Piece

EAN: 6418074086679

SSTL number:

Electric No. Denmark:

Electric No. Sweden: 2506468

ETIM: EC000261 Enclosure/Switchgear cabinet (empty)

Dimensions:

Height (mm): 400

Width (mm): 400

Depth (mm): 210

Height (inch): 15.75

Width (inch): 15.75

Depth (inch): 8.58

Materials:

Material: Polycarbonate

Base colour: RAL 7035 -light grey

Cover colour: RAL 7035 -light grey

Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 120

Temperature °C (continuous): -40 ... 80

Temperature °F (short term): -40 ... 250

Temperature °F (continuous): -40 ... 175

Ratings:

Ingress Protection (EN 60529): IP66;

Impact Resistance (EN 62262): IK10;

Electrical insulation: Totally insulated

Halogen free (DIN/VDE 0472, Part 815): 1

UV resistance: UL 508

Flammability Rating: UL 94 5VA

Glow Wire Test (IEC 60695): 960 °C

NEMA Class: NEMA 1, 4, 4X, 12 and 13

Product is connected to following catalogs:

[ARCA IEC](#) / [ARCA 404021](#) / [ARCA 404021 No MP](#)

CONTACT US

Dimensional Drawings

[Product card \(PDF\)](#)

[FIBOX Arca IEC 404021 DIM](#)

CAD files

Certificates and Declarations

FAQ

Catalogues

Contact

Accessories



IDS ARCA 4040

Inner door set
(380 x 380 x 30)



MPX ARCA
4040

Mounting plate
(350x350 mm)
(350 x 350 x 5)



MPMP ARCA
4040

Mounting plate
multiperforated
(350x350x2 mm -
ø3,6 mm)
(350 x 350 x 2)



DRS ARCA
404021

DIN rail frame set
(385 x 385 x35)

CONTACT US