

M10/16.SFL

[Print View..](#)
[Print to Pdf..](#)

General Information

Extended Product Type:	M10/16.SFL
Product ID:	1SNA115378R0500
EAN:	3472591153781
Catalog Description:	M10/16.SFL Screw Clamp Terminal Blocks - For 6.3 x 32 fuses - Grey
Long Description:	M10/16.SFL Screw Clamp Terminal Blocks Fuse



Categories

Products » Low Voltage Products and Systems » Connection Devices »
Terminal Blocks » Screw Clamp Terminal Blocks

Ordering

EAN:	3472591153781
Minimum Order Quantity:	20 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	16.0 mm
Product Net Height:	68.0 mm
Product Net Depth:	51.5 mm
Product Net Weight:	36.00 g

Container Information

Package Level 1 Units:	20 piece
Package Level 1 Width:	135 mm
Package Level 1 Height:	74 mm
Package Level 1 Length:	175 mm
Package Level 1 Gross Weight:	0.72000 kg
Package Level 1 EAN:	3472591153781
Package Level 2 Units:	300 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	11.3 kg
Package Level 3 Units:	7200 piece
Product Packing Type:	Box

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-10-01
---------------------	--

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity-Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 18-8 AWG

Flammability According to UL94: V0

Additional Information

Color:	Grey
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5-6 mm ² Screw Clamp / Rigid 1x 0.5-10 mm ²
Connection Type:	Screw clamp
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	3500 V
Function:	Fuse
Gauge(s) of Form:	A5
IIT Publishing Status:	Level 0 - Information enabled
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Pollution Degree:	2
Product Main Type:	M10/16.SF
Product Name:	Terminal Block
Rated Cross-Section:	10 mm ²
Rated Current (I _n):	Main Circuit 10 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Voltage (U _r):	750 V
Recommended Screw Driver:	5.5 mm
Spacing:	16 mm
Sub-Function:	For 6.3x32 Fuses
Sub-Function 2:	For blown fuse indicator (to be ordered separately)
Wire Stripping Length:	11.0 mm

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225007C1006
GOST Certificate:	1SND161005A1104
RoHS Information:	1SND230023F0201

Classifications

ETIM 4.0:	EC000899 - Fuse terminal block
ETIM 5.0:	EC000899 - Fuse terminal block
Object Classification Code:	X
