

D4/6.P.T1

[Print View..](#)
[Print to Pdf..](#)

General Information

Extended Product Type:	D4/6.P.T1
Product ID:	1SNA199220R0000
EAN:	3472591992205
Catalog Description:	D4/6.P.T1 Screw Clamp Terminal Blocks - Triple deck - Green-Yellow
Long Description:	D4/6.P.T1 Screw Clamp Terminal Blocks - Ground - Green-Yellow,4mm ² RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail



Categories

Products » Low Voltage Products and Systems » Connection Devices »
Terminal Blocks » Screw Clamp Terminal Blocks

Ordering

EAN:	3472591992205
Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	6.0 mm
Product Net Height:	90.0 mm
Product Net Depth:	64.5 mm
Product Net Weight:	33.00 g

Container Information

Package Level 1 Units:	25 piece
Package Level 1 Width:	147 mm
Package Level 1 Height:	97 mm
Package Level 1 Length:	117 mm
Package Level 1 Gross Weight:	0.82500 kg
Package Level 1 EAN:	3472591992205
Package Level 2 Units:	375 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	12.950 kg
Product Packing Type:	Box

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Technical UL/CSA

Connecting Capacity-Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22-12 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 22-12 AWG

Flammability According to UL94: V0

Additional Information

Color:	Green-Yellow
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22-4 mm ² Screw Clamp / Rigid 1x 0.2-4 mm ²
Connection Type:	Screw clamp
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Function:	Ground
Gauge Type:	A4
IIT Publishing Status:	Level 0 - Information enabled
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	4
Product Main Type:	D4/6.P.T1
Product Name:	Terminal block
Rated Cross-Section:	4 mm ²
Rated Short-time Withstand Current (I _{cw}):	for 1.0s 480 A
Recommended Screw Driver:	4 mm
RoHS Date:	20050818
Spacing:	6 mm
Sub-Function:	7 connections
Sub-Function 2:	Screwless rail connection
Wire Stripping Length:	9.5 mm

Certificates and Declarations (Document Number)

cUL Certificate:	TBD
Declaration of Conformity - CE:	1SND225004C1008
GOST Certificate:	1SND161005A1104
RoHS Information:	1SND230023F0206

Classifications

ETIM 4.0:	EC000901 - Ground terminal block
ETIM 5.0:	EC000901 - Ground terminal block
Object Classification Code:	X
