



Catalog No. 1SVR405510R3050

Description: CR-S024VDC1TRA Pluggable optocoupler Input= 24 V DC, Output= 100 mA/48 V DC

UPC No 4013614486531

Home > Controls & Protective Relays > Interface Relays & Optocouplers

Descriptors

Category	Interface Relays & Optocouplers
----------	---------------------------------

Specifications

Function	Pluggable slim optocoupler CR-S
Rated Control Supply Voltage	24 V DC
Contact material	Transistor
Product Main Type	CR-S
RoHS Status	Following EU Directive 2011/65/EU

Classifications

ETIM 5.0	EC001437 - Switching relay
ETIM 6.0	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	7.0 27371601

Dimensions

Product Net Width	15 mm
Product Net Height	5 mm
Product Net Depth / Length	28 mm
Product Net Weight	0.004kg

Package Information

Package Level 1 Units	10 piece
Package Level 1 Width	23.7 mm
Package Level 1 Height	300 mm
Package Level 1 Depth / Length	7.4 mm
Package Level 1 Gross Weight	0.05 kg
Package Level 1 EAN	4013614509179

Ordering

Minimum Order Quantity	10
Customs Tariff Number	85369095
ECCN	N
ECN	N
ABB MDF Code	3DL - Relays (LV / Control + Protection)
ABB Business Unit	ELSP - Smart Power