



Representative Image

## Alternate Catalog No. B7D-30-01-01 Catalog No. GJL1317001R0011

**Description:** B7D-30-01-01 Mini Contactor 24VDC with diode

**UPC No** 4013614262913

**Home > Contactors & Starters > UL Listed IEC Contactors > AF Contactors**

The B7D-30-01 mini contactor is a compact 3 pole contactor with 1 auxiliary contact and screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The mini contactor has a build-in surge suppressor diode. Further features are the noiseless and hum-free coil, the integrated overvoltage protection, a switch position indication and the integrated possibility for rail or wall mounting.

### Descriptors

|          |               |
|----------|---------------|
| Category | AF Contactors |
|----------|---------------|

### Specifications

|                                                |                                                                                                                                                        |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Type                                   | Mini Contactors (B6, B7)                                                                                                                               |
| General Use Rating UL/CSA                      | (600 V AC) 16 A                                                                                                                                        |
| Object Classification Code                     | Q                                                                                                                                                      |
| Terminal Type                                  | Screw Terminals                                                                                                                                        |
| Rated Control Circuit Voltage                  | 24 V DC                                                                                                                                                |
| Number of Main Contacts NO                     | 3                                                                                                                                                      |
| Connecting Capacity Auxiliary Circuit UL/CSA   | Stranded 1/2x 22-10 american wire gauge                                                                                                                |
| Number of Main Contacts NC                     | 0                                                                                                                                                      |
| Maximum Operating Voltage UL/CSA               | Main Circuit 600 V AC                                                                                                                                  |
| Connecting Capacity Main Circuit UL/CSA        | Stranded 1/2x 22-10 american wire gauge                                                                                                                |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 5 ... 150 Hz                                                                                                                                      |
| Number of Auxiliary Contacts NO                | 0                                                                                                                                                      |
| Connecting Capacity Main Circuit UL/CSA        | Stranded 1/2x 22-10 american wire gauge                                                                                                                |
| RoHS Status                                    | Following EU Directive 2011/65/EU                                                                                                                      |
| Reference Ambient Air Temperature              | Operation -20 ... +55 °C                                                                                                                               |
| Rated Operational Voltage                      | Auxiliary Circuit 12 ... 240 V DC<br>Auxiliary Circuit 12 ... 500 V AC / DC<br>Main Circuit 12 ... 690 V AC / DC<br>Main Circuit 690 V AC              |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 15g                                                                                                                                        |
| Number of Auxiliary Contacts NC                | 1                                                                                                                                                      |
| Tightening Torque UL/CSA                       | Auxiliary Circuit 7 in-lb (pound inch)<br>Control Circuit 7 in-lb (pound inch)<br>Main Circuit 7 in-lb (pound inch)                                    |
| Maximum Operating Altitude Permissible         | 2000 m                                                                                                                                                 |
| Rated Operational Current AC-1                 | (220 / 240 V) 40 °C 20 A<br>(220 / 240 V) 55 °C 16 A<br>(380 / 440 V) 40 °C 20 A<br>(380 / 440 V) 55 °C 16 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |

## Specifications

|                                                    |                                                                                                                                                                                                                 |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                          | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1                                                                                                                            |
| Rated Operational Power AC-3                       | (220 / 230 / 240 V) 3 kW<br>(400 V) 5.5 kW<br>(400 V) Three Phase 5.5 kW<br>(440 V) 5.5 kW<br>(500 V) 5.5 kW<br>(690 V) 3 kW                                                                                    |
| Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1 | 8 x I <sub>e</sub> / AC-3                                                                                                                                                                                       |
| Horsepower Rating UL/CSA                           | (208 V AC) Three Phase 3 hp<br>(220 ... 240 V AC) Single Phase 1.5 hp<br>(220 ... 240 V AC) Three Phase 3 hp<br>(440 ... 480 V AC) Three Phase 5 hp<br>(550 ... 600 V AC) Three Phase 5 hp                      |
| Conventional Free-air Thermal Current              | Main Circuit 20 A                                                                                                                                                                                               |
| Rated Operational Current AC-15                    | (120 V) 4 A<br>(220 / 240 V) 4 A<br>(24 V) 4 A<br>(380 / 400 V) 3 A<br>(500 V) 2 A                                                                                                                              |
| Rated Frequency                                    | Control Circuit DC<br>Main Circuit 60 Hz<br>Main Circuit 50Hz<br>Main Circuit DC                                                                                                                                |
| Rated Short-time Withstand Current                 | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A                                                                                                                                                 |
| Rated Operational Current AC-3                     | (220 / 230 / 240 V) 55 °C 11.3 A<br>(380 / 400 V) 55 °C 11.5 A<br>(440 V) 55 °C 10.1 A<br>(500 V) 55 °C 9.2 A<br>(690 V) 55 °C 3.8 A                                                                            |
| Rated Making Capacity AC-3 acc. to IEC 60947-4-1   | 10 x I <sub>e</sub> / AC-3                                                                                                                                                                                      |
| Maximum Electrical Switching Frequency             | AC-1 300 cycles per hour<br>AC-15 600 cycles per hour<br>AC-3 600 cycles per hour<br>DC-1 600 cycles per hour<br>DC-13 600 cycles per hour<br>DC-3 600 cycles per hour                                          |
| Short-Circuit Protective Devices                   | gG Type Fuses Type 1&2 25 A                                                                                                                                                                                     |
| Rated Insulation Voltage                           | 690 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                   |
| Mechanical Durability                              | 10000000 cycle                                                                                                                                                                                                  |
| Coil Operating Limits                              | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x U <sub>c</sub> (at $\theta \leq 55^\circ \text{C}$ )                                                                                                       |
| Secondary Rated Impulse Withstand Voltage          | Auxiliary Circuit 6 kV<br>Main Circuit 6 kV                                                                                                                                                                     |
| Connecting Capacity Main Circuit                   | Flexible with Ferrule 1/2x 1 ... 2.5 square mm<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 square mm<br>Flexible 1/2x 1 ... 2.5 square mm<br>Rigid 1/2x 1 ... 4 square mm                                 |
| Rated Operational Current DC-13                    | (110 V) 0.7 A<br>(220 / 240 V) 0.4 A<br>(24 V) 2.5 A                                                                                                                                                            |
| Connecting Capacity Control Circuit                | Flexible with Ferrule 1/2x 1 ... 2.5 square mm<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 square mm<br>Flexible 1/2x 1 ... 2.5 square mm<br>Rigid 1/2x 1 ... 4 square mm                                 |
| Coil Consumption                                   | Average Holding Value 50 Hz 3.5 V - A<br>Average Pull-in Value 50 Hz 3.5 V - A                                                                                                                                  |
| Degree of Protection                               | Auxiliary Circuit Terminals IP20<br>Control Circuit Terminals IP20<br>Main Circuit Terminals IP20                                                                                                               |
| Connecting Capacity Auxiliary Circuit              | Flexible with Ferrule 1/2x 1 ... 2.5 square millimetre<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 square millimetre<br>Flexible 1/2x 1 ... 2.5 square millimetre<br>Rigid 1/2x 1 ... 4 square millimetre |
| Mounting on DIN Rail                               | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715                                                                                                  |

## Specifications

Screw Terminal Type

Screw Terminals

Wire Stripping Length

Auxiliary Circuit 9 mm  
Main Circuit 9 mm

## Classifications

ETIM 4

EC000066 - Magnet contactor, AC-switching

ETIM 6.0

EC000066 - Power contactor, AC switching

ETIM 7

EC000066 - Power contactor, AC switching

ETIM 5.0

EC000066 - Magnet contactor, AC-switching

eClass

7.0 27371003

## Dimensions

Product Net Weight

0.175 kg

Product Net Depth / Length

46.5 mm

Product Net Width

52.5 mm

Product Net Height

57.5 mm

## Package Information

Package Level 1 Width

115 mm

Package Level 1 Height

54 mm

Package Level 1 Depth / Length

280 mm

Package Level 1 EAN

4013614420108

Package Level 1 Units

10 piece

Package Level 1 Gross Weight

1.82 kg

## Ordering

Minimum Order Quantity

1

Customs Tariff Number

85365080