



Representative Image

Alternate Catalog No. CE5-10W2 Catalog No. 1SBN010018R1010

Description: CE5-10W2 Auxiliary Contact Block

UPC No 3471522199522

Home > Contactors & Starters > UL Listed IEC Contactors > AF Contactors

The auxiliary contact blocks are used for the operation of auxiliary circuits and control circuits for severe industrial environments. Types of auxiliary contact blocks for front mounting: • CE5 1-pole block, instantaneous with N.O. contact or N.C. contact, available in 2 IP degrees -- CE5 D with built-in microswitch IP40, degree of protection (IP20 on terminals) -- CE5 W with built-in microswitch IP67, degree of protection (IP20 on terminals). The auxiliary contact blocks are equipped with screw type connecting terminals delivered open, protected against accidental direct contact and bear the corresponding function marking.

Descriptors

Category	AF Contactors
Block Contactor Type	Aux Contact

Specifications

Product Type	AF
Object Classification Code	K
Terminal Type	Screw Terminals
Number of Auxiliary Contacts NO	1
RoHS Status	Following EU Directive 2011/65/EU
Number of Auxiliary Contacts NC	0
Rated Operational Current AC-15	(220 / 240 V) 2 A (24 / 127 V) 2 A

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 6.0	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 5.0	EC002498 - Accessories for low-voltage switch technology

Dimensions

Product Net Weight	0.02kg
--------------------	--------

Package Information

Package Level 1 EAN	3471522199522
Package Level 1 Units	1 piece
Package Level 2 Units	126 piece
Package Level 3 Units	4536 piece
Package Level 2 Gross Weight	2.52 kg

Ordering

Minimum Order Quantity	1
------------------------	---