



Alternate Catalog No. DP30C1P-1 Catalog No. 1SBX103100R1200

Description: DP CONTR,30A,1P,120/60

UPC No 662019754154

 $\label{loss:eq:home} \mbox{Home} > \mbox{Contactors} \ \& \ \mbox{Starters} > \mbox{Definite Purpose Contactor}$

DP30C1P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Descriptors	
Category	Definite Purpose Contactor
Specifications	
Product Type	DP Contactor
Amps Frame	30 A
Poles	1P
Coil Voltage	120 V
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#10-32 combo screw with Quad quick connector
Classifications	
UL / cUL Certifcation	UL / cUL _ E224401
Dimensions	
Length	2.07 in.
Width	3.26 in.
Height	2.36 in.
Moraht	
Weight	0.5 lb.
Operating Performance	0.5 lb.
	-40+65 oC
Operating Performance	
Operating Performance Operating temperature	-40+65 oC

electrification.us.abb.com Created on: 09/30/2024

electrification.us.abb.com Created on: 09/30/2024