



Alternate Catalog No. DP40C2P-1 Catalog No. 1SBX104200R1200

Description: DP CONTR,40A,2P,120/60

UPC No 662019754215

 $\label{loss:eq:home} \mbox{Home} > \mbox{Contactors} \ \& \ \mbox{Starters} > \mbox{Definite Purpose Contactor}$

DP40C2P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Category	Definite Purpose Contactor
Specifications	
Product Type	DP Contactor
Amps Frame	40 A
Poles	2P
Coil Voltage	120 V
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#14-4 AWG lug with quad quick connectors
UL / cUL Certification Dimensions	UL / cUL _ E224401
	2.07 in.
Length Width	3.26 in.
Height	2.36 in.
Weight	0.6 lb.
Operating Performance	
Operating temperature	-40+65 oC
Insulation Class	130 oC Class B
Ordering	

electrification.us.abb.com Created on: 09/30/2024

electrification.us.abb.com Created on: 09/30/2024