



## Alternate Catalog No. DP40C3P-1 Catalog No. 1SBX104300R1200

Description: DP CONTR,40A,3P,120/60

UPC No 662019749457

 $\label{loss:eq:home} \mbox{Home} > \mbox{Contactors} \ \& \ \mbox{Starters} > \mbox{Definite Purpose Contactor}$ 

DP40C3P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Category	Definite Purpose Contactor
Specifications	
Product Type	DP Contactor
Amps Frame	40 A
Poles	3P
Coil Voltage	120 V
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#14-4 AWG lug with dual Quick connectors
Dimensions	UL / cUL _ E224401
Length	3.622 in.
Width	2.37 in.
Height	2.91 in.
Weight	1 lb.
Operating Performance	
Operating temperature	-40+65 oC
Insulation Class	130 oC Class B
Ordering	
Customs Tariff Number	85365080

electrification.us.abb.com Created on: 09/30/2024

electrification.us.abb.com Created on: 09/30/2024