



Alternate Catalog No. DP60C3P-2 Catalog No. 1SBX106300R1300

Description: DP CONTR,60A,3P,240/208V

UPC No 662019755687

 $\label{loss:eq:home} \mbox{Home} > \mbox{Contactors} \ \& \ \mbox{Starters} > \mbox{Definite Purpose Contactor}$

DP60C3P-2 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Category	Definite Purpose Contactor
Category	Definite Fulpose Contactor
Specifications	
Product Type	DP Contactor
Amps Frame	60 A
Poles	3P
Coil Voltage	208/240Vac
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#14-2 lug with dual Quick Connectors
UL / cUL Certification Dimensions	UL / cUL _ E224401
Length	3.77 in.
Width	2.76 in.
Height	3.3 in.
Weight	1.4 lb.
Operating Performance	
Operating temperature	-40+65 oC
Insulation Class	130 oC Class B
Ordering	
Customs Tariff Number	85365080

electrification.us.abb.com Created on: 09/30/2024

electrification.us.abb.com Created on: 09/30/2024