

F202 A S-63/0,1



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs
Residual Current Devices RCDs

General Information

Extended Product Type: F202 A S-63/0,1

Product ID: 2CSF202201R2630

EAN: 8012542823001

Catalog Description: F202 A S-63/0,1 Residual Current Dev.

Long Description: The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

Additional Information

Country of Origin:	Italy (IT)
Customs Tariff Number:	85363030
Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5602
EAN:	8012542823001
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Ground fault current circuit breaker
EPLAN Function Definition:	Ground fault current circuit-breaker / Ground fault current circuit breakers, 4 connection points / Ground fault current circuit breaker, two-pole 1/2 2/1 3/4 4/3
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
Environmental Information:	S-P-00080
Instructions and Manuals:	2CSF423001D6406
Invoice Description:	F202 A S-63/0,1 Residual Current Dev.
Maximum Operating Voltage UL/CSA:	277 V AC
Minimum Order Quantity:	1 piece
Number of Poles:	2
Object Classification Code:	Q
Operating Characteristic:	Selective
Options Provided:	-
Package Level 1 EAN:	8012542823001
Package Level 1 Gross Weight:	0.225 kg
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.041 m
Power Loss:	at Rated Operating Conditions per Pole 3.2 W
Product Main Type:	F200
Product Name:	Residual Current Circuit Breaker
Product Net Depth:	0.069 m
Product Net Height:	0.085 m
Product Net Weight:	0.200 kg
Product Net Width:	0.035 m
Rated Current (I_n):	63 A
Rated Frequency (f):	50 ... 60 Hz
Rated Operational Voltage:	230 V AC
Rated Residual Current:	100 mA
Rated Voltage (U_r):	230/400 V
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	Residual Current Device F202 A S-63/0,1
Standards:	IEC/EN 61008 UL 1053
Type of Residual Current:	A type
Accessories Available:	Yes

