OS1200L30



Products + Low Voltage Products and Systems + Switches + Switch Fuses

General Information

Extended Product Type: OS1200L30

Product ID: 1SCA109345R1001 **EAN**: 6417019425184

Catalog Description: OS1200L30 Fusible disconnect switch

Long Description: Switch Fuses, Front Operated, 3-pole, 30 (Right Side), Class L, 1200 A, Handl

e and shaft not included,

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC311127D0202

Instructions and Manuals: 1SCC311022M0206

Dimensions

Product Net Width: 429 mm

Product Net Height: 426 mm

Product Net Depth: 294 mm

Product Net Weight: 31.23 kg

68.85 lb

Technical

Rated Operational Current AC-23A (380 ...

(380 ... 415 V) 1000 A

(l_e):

(l_e):

(P_e):

(500 V) 1000 A (690 V) 1000 A

Rated Operational Current AC-23B

(380 ... 415 V) 1000 A

(500 V) 1000 A (690 V) 1000 A

Rated Operational Power AC-23A

(220 ... 240 V) 315 kW

(400 V) 560 kW (415 V) 560 kW

(500 V) 710 kW (690 V) 1000 kW

Conventional Free-air Thermal

Current (Ith):

q = 40 °C 1250 A

Conventional Thermal Current Fully Enclosed 1000 A

 (I_{the}) :

Rated Impulse Withstand Voltage (U _{imp}):	12 kV
Rated Insulation Voltage (U _i):	1000 V
Rated Operational Voltage:	690 V AC
Power Loss:	at Rated Operating Conditions per Pole 75 W
Pollution Degree:	3
Handle Type:	Handle and shaft not included
Switches Operating Mechanism:	30 (Right Side)
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Fuse Size:	1200 A
Fuse System:	Class L
Operating Mode:	Front Operated
Standards:	UL98
Mounting Type:	Base mounting
Number of Poles:	3
Terminal Type:	Lug terminals
Terminal Width:	50 mm
Technical UL/CSA	
Ampere Rating UL/CSA:	1200 A
Tightening Torque UL/CSA:	Wire-Clamp 500 in·lb Cable Lug 480 in·lb
Certificates and Declarations (Declarations)	ocument Number)
CCC Certificate:	CCC OS1200-1250 2015.pdf
Declaration of Conformity - CE:	1SCC311127D2703
EAC Certificate:	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_O S_OSMpdf
Instructions and Manuals:	1SCC311022M0206
RoHS Information:	1SCC311108D0203
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	444 mm 17.48 in
Package Level 1 Length:	714 mm 28.11 in
Package Level 1 Height:	385 mm 15.16 in

Package Level 1 Gross Weight: 34.43 kg

75.91 lb

Package Level 1 EAN: 6417019425184

Classifications

Object Classification Code: Q

ETIM 5: EC001040 - Fuse switch disconnector

ETIM 6: EC001040 - Fuse switch disconnector

ETIM 7: EC001040 - Fuse switch disconnector

