OS125GF12



Products + Low Voltage Products and Systems + Switches + Switch Fuses

General Information

Extended Product Type: OS125GF12

Product ID: 1SCA115609R1001 **EAN**: 6417019479569

Catalog Description: OS125GF12 Switch fuse

Long Description: Switch Fuses, Front Operated, 3-pole, 12 (Between the Poles), NFC, 22x58, H

andle and shaft not included,

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC311137D0201

Instructions and Manuals: 1SCC110037M0206

Dimensions

Product Net Width: 147 mm

Product Net Height: 140 mm

Product Net Depth: 130 mm

Product Net Weight: 1.84 kg

4.06 lb

Technical

(l_e):

(l_e):

Rated Operational Current AC-21A (380 ...

(380 ... 415 V) 125 A

(I_e):

(500 V) 125 A (690 V) 125 A

Rated Operational Current AC-22A

(380 ... 415 V) 125 A (500 V) 125 A

(000) () 405 A

(690 V) 125 A

Rated Operational Current AC-23A

(380 ... 415 V) 125 A

(500 V) 125 A

(690 V) 125 A

Rated Operational Power AC-23A

(220 ... 240 V) 37 kW

(P_e): (400 V) 55 kW

(415 V) 55 kW (500 V) 75 kW

(690 V) 110 kW

Conventional Free-air Thermal Current (I _{th}):	q = 40 °C 125 A
Conventional Thermal Current (I _{the}):	Fully Enclosed 125 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Insulation Voltage (U _i):	1000 V
Rated Operational Voltage:	690 V AC
Rated Short-time Withstand Current (I _{cw}):	for 1 s 5 kiloampere rms
Power Loss:	at Rated Operating Conditions per Pole 5 W
Pollution Degree:	3
Handle Type:	Handle and shaft not included
Switches Operating Mechanism:	12 (Between the Poles)
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Fuse Size:	22x58
Fuse System:	NFC
Operating Mode:	Front Operated
Standards:	IEC 60947-3
Mounting Type:	Base mounting
Number of Poles:	3
Terminal Type:	Lug terminals
Terminal Width:	20 mm
Tightening Torque:	15 22 N·m
Certificates and Declarations ([Document Number)
CCC Certificate:	CCC OS100-160G_ 2015.pdf

С

CCC Certificate.	CCC OS 100-160G_ 2015.pdf
Declaration of Conformity - CE:	1SCC311137D2703
DNV GL Certificate:	1SCC311125D0203
EAC Certificate:	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_O S_OSMpdf
Instructions and Manuals:	1SCC110037M0206
RoHS Information:	1SCC311108D0203

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	192 mm 7.56 in
	7.30 III

 Package Level 1 Length:
 192 mm

 7.56 in
 7.56 in

 Package Level 1 Height:
 146 mm

 5.75 in
 5.75 in

 Package Level 1 Gross Weight:
 1.94 kg

 4.28 lb
 4.28 lb

Classifications

ETIM 7:

Object Classification Code:

ETIM 5: EC001040 - Fuse switch disconnector

ETIM 6: EC001040 - Fuse switch disconnector

EC001040 - Fuse switch disconnector

