

Products → Low Voltage Products and Systems → Switches → Switch Disconnectors

General Information

Extended Product Type:	OT2000U03
Product ID:	1SCA117313R1001
EAN:	6417019493336
Catalog Description:	OT2000U03 switch-disconnector
Long Description:	3-pole, front operated, base mounted non-fusible disconnect switch, handle and shaft are not included, terminal bolt kit included

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Popular Downloads

Instructions and Manuals:	1SCC301094M0202
----------------------------------	-----------------

Dimensions

Product Net Width:	800 mm 31.5 in
Product Net Height:	1001 mm 39.4 in
Product Net Depth / Length:	335 mm 13.2 in
Product Net Weight:	52 kg

Technical

Pollution Degree:	3
Handle Type:	Handle and shaft not included
Switches Operating Mechanism:	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Operating Mode:	Front operated
Standards:	UL 98
Special Functions:	No
Mounting Type:	Base mounting
Number of Poles:	3

Terminal Type: Lug terminals

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	600 V
Ampere Rating UL/CSA:	2000 A
Tightening Torque UL/CSA:	500 in·lb

Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC301094M0202

Container Information

Package Level 1 Width:	394 mm 15.51 in
Package Level 1 Depth / Length:	584 mm 22.99 in
Package Level 1 Height:	385 mm 15.16 in
Package Level 1 EAN:	6417019493336

Classifications

ETIM 5:	EC000216 - Switch disconnect
ETIM 6:	EC000216 - Switch disconnect
ETIM 7:	EC000216 - Switch disconnect

