## OT200ES03



Products + Low Voltage Products and Systems + Switches + Switch Disconnectors

General Information

Extended Product Type: OT200ES03

Product ID: 1SCA022860R0200 EAN: 6417019308722

Catalog Description: OT200ES03 switch-disconnector

**Long Description:** 3-pole, side operated, base mounted switch-diconnector, handle and shaft

are not included, terminal bolt kit included

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC301020C0201

Instructions and Manuals: 1SCC301068M0203

**Dimensions** 

Product Net Width: 199 mm

Product Net Height: 150 mm

Product Net Depth: 82 mm

Product Net Weight: 1.54 kg

3.4 lb

**Technical** 

Rated Operational Current AC-21A (380 ...

(380 ... 415 V) 200 A

(l<sub>e</sub>):

(l<sub>e</sub>):

(500 V) 200 A (690 V) 200 A (1000 V) 200 A

**Rated Operational Current AC-22A** 

(380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

Rated Operational Current AC-23A

(500 V) 200 A

(I<sub>e</sub>): (380 ... 415 V) 200 A

(690 V) 200 A

Rated Operational Power AC-23A

(380 ... 415 V) 110 kW

 $(P_e)$ : (500 V) 132 kW

(690 V) 200 kW

**Conventional Free-air Thermal** 

Current (Ith):

q = 40 °C 200 A

Conventional Thermal Current (I <sub>the</sub> ):	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	12 kV
Rated Insulation Voltage (U <sub>i</sub> ):	1000 V
Rated Operational Voltage:	1000 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> ):	(690 V AC) 30 kA
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 8 kiloampere rms
Power Loss:	at Rated Operating Conditions per Pole 4 W
Pollution Degree:	3
Handle Type:	Handle and shaft not included
Switches Operating Mechanism:	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Operating Mode:	Side operated
Standards:	IEC 60947-3
Special Functions:	No
Mounting Type:	Base mounting
Number of Poles:	3
Terminal Type:	Lug terminals
Tightening Torque:	15 22 N·m
Environmental	
Environmental Information:	1SCC301149D0202
Certificates and Declarations (I	Document Number)
Declaration of Conformity - CE:	1SCC301131D2705
DNV GL Certificate:	1SCC301174D0204
Environmental Information:	1SCC301149D0202
Instructions and Manuals:	1SCC301068M0203
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	170 mm
Package Level 1 Length:	250 mm
Package Level 1 Height:	115 mm

Package Level 1 Gross Weight: 1.84 kg

4.06 lb

Package Level 1 EAN: 6417019308722

Classifications

Object Classification Code: Q

ETIM 5: EC000216 - Switch disconnector

ETIM 6: EC000216 - Switch disconnector

