OT800U30



Products + Low Voltage Products and Systems + Switches + Switch Disconnectors

General Information

Extended Product Type: OT800U30

Product ID: 1SCA105640R1001 EAN: 6417019395739

OT800U30 Non-fusible disconnect switch **Catalog Description:** Handle and shaft must be ordered separatly. Long Description:

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC301020C0201

Instructions and Manuals: 1SCC301047M0205

Dimensions

Product Net Width: 266 mm

Product Net Height: 372 mm

Product Net Depth / Length: 127 mm

Product Net Weight: 17.18 kg

37.88 lb

Technical

(l_e):

(P_e):

Rated Operational Current AC-22A (380 ... 415 V) 1600 A

(l_e): (500 V) 1600 A

(690 V) 1600 A

Rated Operational Current AC-23A

(380 ... 415 V) 1250 A

(500 V) 1250 A (690 V) 1250 A

Rated Operational Power AC-23A

(380 ... 415 V) 710 kW

(500 V) 900 kW (690 V) 1200 kW

Rated Impulse Withstand Voltage

12 kV

 (U_{imp}) :

1000 V Rated Insulation Voltage (Ui):

1000 V **Rated Operational Voltage:**

Rated Short-Circuit Making (690 V AC) 110 kA

Capacity (I_{cm}):

Rated Short-time Withstand Current (I _{cw}):	for 1 s 50 kiloampere rms
Power Loss:	29 W
Pollution Degree:	3
Handle Type:	Handle and shaft not included
Switches Operating Mechanism:	Mechanism at the End of the Switch 30 (Right Side)
Distance Between Phases:	Standard
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Operating Mode:	Front operated
Standards:	IEC&UL
Special Functions:	No
Mounting Type:	Base mounting
Number of Poles:	3
Terminal Type:	Lug terminals
Technical UL/CSA Horsepower Rating UL/CSA:	(acc. to UL 240 V) 200 Hp (acc. to UL 480 V) 500 Hp (acc. to UL 600 V) 500 Hp
Ampere Rating UL/CSA:	800 A
Environmental	
Environmental Information:	1SCC301149D0202
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE:	1SCC301161D0202
Environmental Information:	1SCC301149D0202
Instructions and Manuals:	1SCC301047M0205
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	400 mm 15.75 in
Package Level 1 Depth / Length:	435 mm 17.13 in
Package Level 1 Height:	170 mm 6.69 in
Package Level 1 Gross Weight:	18.48 kg 40.74 lb

Package Level 1 EAN: 6417019395739

Classifications

Object Classification Code: Q

ETIM 5: EC000216 - Switch disconnector

ETIM 6: EC000216 - Switch disconnector

ETIM 7: EC000216 - Switch disconnector











