

Alternate Catalog No. PSTX840-690-70
Catalog No. 1SFA898219R7000

Description: PSTX840, 690V, 100-250VAC

UPC No 7320500510414

Home > Soft Starters > Softstarter - Open (PSTX)



Representative Image

Descriptors

Category	Softstarter - Open (PSTX)
----------	---------------------------

Specifications

Product Type	Soft Starters
Input Voltage	208-690 V
Control Voltage	100-250 V
Normal Duty: Output Current (A)	840
Normal Duty: Motor Power (HP) at 208V	300
Normal Duty: Motor Power (HP) at 230V	350
Normal Duty: Motor Power (HP) at 460V	700
Normal Duty: Motor Power (HP) at 575V	800
Heavy Duty: Output Current (A)	720
Heavy Duty: Motor Power (HP) at 208V	250
Heavy Duty: Motor Power (HP) at 230V	300
Heavy Duty: Motor Power (HP) at 460V	600
Heavy Duty: Motor Power (HP) at 575V	700
Power Dissipation In Watts	106
Height (Inches)	19.3
Width (Inches)	17.1
Depth (Inches)	14.5

Classifications

RoHS Indicator	Yes
UL/CUL Listing	Yes

Dimensions

Weight (lb)	101.8
Height (mm)	490
Width (mm)	435
Depth (mm)	369

Dimensions

Weight (kg)

46.2