



Representative

**Catalog Number:** S201MUC-C63  
**UPC Number:** 88861427344  
**Status:** Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 63 Amps, 1 Pole, Interrupt Rating 10 kA, Thermal Magnetic Trip Curve C, Voltage up to 277/Y480 VAC, 250/500 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 1077, CSA 22.2 No. 235

## North American Specifications (UNSPSC)

|                       |                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------|
| UNSPSC                | 39121603 Miniature circuit breakers                                                                           |
| IGCC                  | 4897 Miniature circuit breakers                                                                               |
| Brand Name            | ABB                                                                                                           |
| Type                  | High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection                      |
| Special Features      | Equipped with Permanent Magnets that Assist in the Forced Extinguishing of the Arc.                           |
| Application           | Supplementary Protective Devices. Protection and Control of the Circuits Against Overloads and Short-Circuits |
| Standard              | UL 1077, CSA 22.2 No. 235                                                                                     |
| Voltage Rating        | 277/Y480 VAC, 250/500 VDC                                                                                     |
| Amperage Rating       | 63 Amps                                                                                                       |
| Trip Type             | C                                                                                                             |
| Interrupt Rating      | 10 kA                                                                                                         |
| Number Of Poles       | 1                                                                                                             |
| Auxiliary Contacts    | Yes                                                                                                           |
| Length                | 69 Millimeters                                                                                                |
| Width                 | 17.5 Millimeters                                                                                              |
| Height                | 88 Millimeters                                                                                                |
| Operating Temperature | -25 to +55 Degrees Celcius                                                                                    |

## Packaging

|                           |               |
|---------------------------|---------------|
| Inner Quantity            | 1             |
| Inner Dimensions (inches) | 3.15x.72x4.13 |
| Outer Quantity            | 10            |
| Outer Dimensions (inches) | 3.15x7.2x4.13 |
| Weight Uom                | 0.3 lbs. Each |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)