



Representative

Catalog Number: S202MUC-K6
UPC Number: 88861426068
Status: Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 6 Amps, 2 Pole, Interrupt Rating 10 kA, Thermal Magnetic Trip Curve K, Voltage up to 277/Y480 VAC, 250/500 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 1077, CSA 22.2 No. 235

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	Equipped with Permanent Magnets that Assist in the Forced Extinguishing of the Arc.
Application	Supplementary Protective Devices. Protection and Control of the Circuits Like Motors, Transformers and Auxiliary Circuits, Against Overloads and Short-Circuits.
Standard	UL 1077, CSA 22.2 No. 235
Voltage Rating	277/Y480 VAC, 250/500 VDC
Amperage Rating	6 Amps
Trip Type	K
Interrupt Rating	10 kA
Number Of Poles	2
Auxiliary Contacts	Yes
Length	69 Millimeters
Width	35 Millimeters
Height	88 Millimeters
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	5
Outer Dimensions (inches)	3.15x7.2x4.13
Weight Uom	0.48 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com