



Representative

Catalog Number: S202UDC-Z32
UPC Number: 80432557037
Status: Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 32 Amps, 2 Pole, Interrupt Rating 14 kA, Trip Curve K, Electromechanic Tripping Mechanism for Short Circuit Protection, Voltage up to 60/125 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 489, CSA 22.2 No. 5

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed to Provide Maximum Protection with a Very Low Short Circuit Trip Setting; Example: Semiconductors, Control Circuits
Standard	UL 489, VDE 0660, IEC 60947-2
Voltage Rating	60/125 VDC
Amperage Rating	32 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	14 kA
Number Of Poles	2
Auxiliary Contacts	Yes
Length	71 Millimeters
Width	35 Millimeters
Height	92 Millimeters
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	64.5 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com