

S804S-UCK20



Products Low Voltage Products and Systems Modular DIN Rail Products High Performance Circuit Breakers HPCBs

General Information

Extended Product Type:	S804S-UCK20
Product ID:	2CCS864001R1487
EAN:	7612271203719
Catalog Description:	S804S-UCK20
Long Description:	S804S-UCK20 High Performance Miniature Circuit Breaker 4 Poles K Characteristic 20A 50 kA 250VDC

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
Connecting Capacity:	Flexible 1 ... 50 mm ² Flexible Stranded 1 ... 70 mm ²
Contact Position Indication:	ON / OFF / TRIP
Country of Origin:	Switzerland (CH)
Customs Tariff Number:	85362020
Data Sheet, Technical Information:	2CCC413003C0203
Declaration of Conformity - CE:	2CCC413016D0601
Dimension Diagram:	2CCC413003C0201
EAN:	7612271203719
EPLAN Catalog Tree:	Electrical engineering / Protection devices / General
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Environmental Information:	2CCY413201D0201
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CCC413016M0002
Invoice Description:	S804S-UCK20
Minimum Order Quantity:	1 piece
Number of Poles:	4
Object Classification Code:	F
Package Level 1 EAN:	7612271203719
Package Level 1 Gross Weight:	1010 g
Package Level 1 Height:	99 mm
Package Level 1 Length:	111 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 2 Units:	1
Power Loss:	14 W
Product Depth:	88 mm
Product Main Type:	S800S
Product Name:	High Performance MCB
Product Net Depth:	82.5 mm
Product Net Height:	95 mm

Product Net Length:	108 mm
Product Net Weight:	0.98 kg
Product Net Width:	106 mm
Rated Current (I_n):	20 A
Rated Operational Current (I_e):	20 A
Rated Operational Voltage:	1000 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(750 V DC) 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(750 V DC) 50 kA
Rated Voltage (U_r):	230 / 400 V
RoHS Information:	2CCC413008D0201
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 4 - Rated operational current 20A - Rated operational voltage 1000V DC
Size:	4 modules
Standards:	IEC/EN 60947-2
Tripping Characteristic:	UC-K
Type of Residual Current:	standard version
Actuator Marking:	I / O

