

S804U-UCZ25



Products Low Voltage Products and Systems Modular DIN Rail Products High Performance Circuit Breakers HPCBs

General Information

Extended Product Type:	S804U-UCZ25
Product ID:	2CCS248359R0001
EAN:	7612271420734
Catalog Description:	S804U-UCZ25
Long Description:	S804U-UCZ25 4 Pole Z Characteristic 25A 10kA 600VDC High Performance Circuit Breaker HPCB

Additional Information

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
Connecting Capacity:	Flexible 1 ... 50 mm ² Flexible Stranded 1 ... 70 mm ²
Contact Position Indication:	ON / OFF / TRIP
Country of Origin:	Switzerland (CH)
Customs Tariff Number:	85362020
Data Sheet, Technical Information:	2CCC413003C0203
Declaration of Conformity - CE:	2CCC413033D0601
EAN:	7612271420734
EPLAN Catalog Tree:	Electrical engineering / Protection devices / General
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Environmental Information:	2CCY413201D0202
Instructions and Manuals:	2CCC413032M0401
Invoice Description:	S804U-UCZ25
Minimum Order Quantity:	1 piece
Number of Poles:	4
Object Classification Code:	F
Package Level 1 EAN:	7612271420734
Package Level 1 Gross Weight:	1010 g
Package Level 1 Height:	99 mm
Package Level 1 Length:	111 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	150 mm
Power Loss:	6 W
Product Main Type:	S800U
Product Name:	High Performance MCB
Product Net Depth:	82.5 mm
Product Net Height:	142 mm
Product Net Length:	106 mm
Product Net Weight:	0.98 kg
Product Net Width:	106 mm
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Operational Current (I_e):	25 A
Rated Operational Voltage:	600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(600 V DC) 10 kA
RoHS Information:	2CCC413012D0601
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	High Performance Circuit Breaker - S800U - Tripping characteristic Z - Number of poles 4 - Rated operational current 25A - Rated operational voltage 600V DC
Standards:	UL 489
Tripping Characteristic:	Z
Actuator Marking:	I / O

