



Representative

Catalog Number: SU202M-C40
UPC Number: 88861442252
Status: Active

Miniature Circuit Breaker, Rated Current 40 Amps, 2 Pole, Interrupt Rating 10 kA, Trip Curve C, Voltage up to 277/Y480 VAC, 48/96 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 489, CSA 22.2 No. 5

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Branch Circuit Protection
Standard	UL 489, CSA 22.2 No. 5, IEC 60947-2
Voltage Rating	277/Y480 VAC, 48/96 VDC
Amperage Rating	40 Amps
Trip Type	C
Interrupt Rating	10 kA
Number Of Poles	2
Auxiliary Contacts	Yes
Length	69 Millimeters
Width	35 Millimeters
Height	111 Millimeters
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Inner Quantity	1
Inner Dimensions (inches)	3.15x1.44x4.13
Outer Quantity	5
Outer Dimensions (inches)	7.5x4.8x3.2
Weight Uom	0.57 lbs. Each

Documents / Support Tools

Technical Data Sheet Global	Available on Website
Marketing Brochure US 1	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com