

SU203MR-K30



Products Low Voltage Products and Systems Modular DIN Rail Products Miniature Circuit Breakers MCBs

General Information

Extended Product Type:	SU203MR-K30
Product ID:	2CDS273347R0527
EAN:	4016779958530
Catalog Description:	Miniature Circuit Breakers MCBs - SU200MR - 3P - K
Long Description:	SU203MR-K30 MCB K-Char., 10kA, 30A, 3P, RTT UL 489, Ring Cable Lug

Additional Information

CSA Certificate:	2CDZ405000A0575
Country of Origin:	Germany (DE)
Customs Tariff Number:	85362010
Data Sheet, Technical Information:	2CDC002184D0202
Declaration of Conformity - CE:	2CDK400616D2702
EAN:	4016779958530
EPLAN Catalog Tree:	Electrical engineering / Protection devices / General
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Instructions and Manuals:	2CDC002184D0202
Invoice Description:	SU203MR-K30 MCB K-Char., 10kA, 30A, 3P, RTT
Minimum Order Quantity:	1 piece
Number of Poles:	3
Number of Protected Poles:	3
Options Provided:	Ring tongue
Package Level 1 EAN:	4016779961073
Package Level 1 Gross Weight:	1.32 kg
Package Level 1 Height:	82 mm
Package Level 1 Length:	191 mm
Package Level 1 Units:	3 piece
Package Level 1 Width:	121 mm
Package Level 2 EAN:	4016779981040
Package Level 2 Gross Weight:	16 kg
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Units:	27 piece
Package Level 2 Width:	275 mm
Power Loss:	at Rated Operating Conditions per Pole 3.5 W
Product Main Type:	SU200MR
Product Name:	Miniature Circuit Breakers MCBs
Product Net Depth:	71 mm
Product Net Height:	115 mm
Product Net Weight:	0.42 kg
Product Net Width:	52.5 mm
Rated Current (I_n):	30 A
Recommended Screw Driver:	Pozidriv 2
Screw Terminal Type:	Ring-Tongue Terminal with Captive Screw
Selling Unit of Measure:	piece
Terminal Type:	Ring-Tongue Terminals
Tripping Characteristic:	K
UL Certificate:	2CDZ405000A0085
UNSPSC:	39121614
Width in Number of Modular Spacings:	3
eClass:	7.0 27141901
Accessories Available:	Yes

