

Catalog Number: XT1HU3125DFF000XXX
UPC Number: 88861440264
Status: Active

Tmax XT Molded Circuit Breaker, Frame Size XT1 - to 125A, 600Y/347V (UL) / 160A, 690V (IEC), Trip Type Molded case switch disconnecter, 3 Poles

North American Specifications (UNSPSC)

UNSPSC	39121616 Molded case circuit breakers
IGCC	4927 Molded case circuit breakers
Brand Name	ABB
Sub Brand	Tmax XT
Type	Molded case circuit breaker
Special Features	Feature high specific let-through current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way.
Application	Ideal solution for all distribution levels from the main low voltage switchboard to the subswitchboards in the installation
Standard	UL 80% rated / IEC dual rated
Frame	XT1 - to 125A, 600Y/347V (UL) / 160A, 690V (IEC) - Thermal magnetic protection
Trip Type	Molded case switch disconnecter
Number Of Poles	3 Poles

Packaging

Outer Quantity	1
Outer Dimensions (inches)	5.63x5.04x5.31
Weight Uom	2.43 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com