

**Catalog Number:** XT2HU3080BFF000XXX  
**UPC Number:** 88861440429  
**Status:** Active

Tmax XT Molded Circuit Breaker, Frame Size XT2 - to 125A, 600V (UL) / 160A (IEC), 690V ,  
Trip Type Thermal magnetic adjustable (TMD/TMA), 3 Poles

**North American Specifications (UNSPSC)**

|                  |                                                                                                                                                                      |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC           | 39121616 Molded case circuit breakers                                                                                                                                |
| IGCC             | 4927 Molded case circuit breakers                                                                                                                                    |
| Brand Name       | ABB                                                                                                                                                                  |
| Sub Brand        | Tmax XT                                                                                                                                                              |
| Type             | Molded case circuit breaker                                                                                                                                          |
| Special Features | Feature high specific let-trough current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way. |
| Application      | Ideal solution for all distribution levels from the main low voltage switchboard to the subswitchboards in the installation                                          |
| Standard         | UL 80% rated / IEC dual rated                                                                                                                                        |
| Frame            | XT2 - to 125A, 600V (UL) / 160A (IEC), 690V - Thermal magnetic and Electronic protection                                                                             |
| Trip Type        | Thermal magnetic adjustable (TMD/TMA)                                                                                                                                |
| Number Of Poles  | 3 Poles                                                                                                                                                              |

**Packaging**

|                           |                |
|---------------------------|----------------|
| Outer Quantity            | 1              |
| Outer Dimensions (inches) | 5.71x5.12x8.19 |
| Weight Uom                | 3.72 lbs. Each |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com