



Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 14kVA

By Acme Electric
Catalog # [DTFA0142S](#)



Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 14kVA.

Features

- Copper terminations for trouble free operation
- Wound Core and Strip Winding for Low Losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units

General

ANFC Taps	1
BNFC Taps	1
Catalog Number	DTFA0142S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	230Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	230Y/133 V
Taps % Steps	5%
UL Insulation Class	180°C
UPC	047503000632
Winding Material	AL
kVA	14

Dimensions

Dimensions	9.03 in x 20.3 in x 18.86 in
Height	18.86 in
Length	9.03 in
Weight	1 lb

Width 20.3 in

Electrical Ratings

Frequency Rating 60 Hz
Primary Voltage 230D V

Certifications And Compliance

CSA Standard C22.2 No. 47
Nema Rating NEMA 3R
UL Standard UL 506

Logistics

Carton Quantity 1
Pallet Quantity 4

Product Assets

[Brochures - Drive Isolation Transformers](#)
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - Acme_DTFA0142S_TECHNICAL_DRAWINGS](#)
[SDS - HCC SDS](#)
[Specifications - DTFA0142S Specification Sheet](#)
[Specifications - DTFA0142S](#)
[Specifications - DTFA0142S Specification Sheet French](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand