



Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 34kVA

By Acme Electric
Catalog # [DTFA0344S](#)

Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 34kVA.

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA1

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTFA0344S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	230Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	230Y/133 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000687
Winding Material	AL
kVA	34

Dimensions

Dimensions	19.37 in x 24.39 in x 25.5 in
Height	25.5 in
Length	19.37 in
Weight	330 lb



*Representative Image

Width	24.39 in
-------	----------

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	230D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

- [Brochures - Drive Isolation Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_DTFA0344S_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - DTFA0344S Specification Sheet French](#)
- [Specifications - DTFA0344S Specification Sheet](#)
- [Specifications - DTFA0344S](#)
- [Terms and Conditions - HCC Terms & Conditions](#)