



## Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 51kVA

By Acme Electric  
Catalog # [DTFA0514S](#)

Drive Isolation Transformer - Three Phase, 230Δ - 230Y/133V, 51kVA.



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA2

### General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTFA0514S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	230Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	230Y/133 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503089880
Winding Material	AL
kVA	51

### Dimensions

Dimensions 22.37 in x 28.15 in x 29.9 in

Height	29.9 in
Length	22.37 in
Weight	375 lb
Width	28.15 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	230D V

### Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

### Product Assets

[Brochures - Drive Isolation Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Engineering Drawing - Acme\\_DTFA0514S\\_TECHNICAL\\_DRAWINGS](#)  
[SDS - HCC SDS](#)  
[Specifications - DTFA0514S Specification Sheet](#)  
[Specifications - DTFA0514S Specification Sheet French](#)  
[Specifications - DTFA0514S](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand