



Drive Isolation Transformer - Three Phase, 460Δ - 230Y/133V, 75kVA

By Acme Electric
Catalog # [DTGA0754S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 230Y/133V, 75kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA2

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGA0754S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	230Y/133 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	004750369530
Winding Material	AL
kVA	75

Dimensions

Dimensions	22.37 in x 28.15 in x 29.9 in
Height	29.9 in
Length	22.37 in
Weight	570 lb

Width	28.15 in
-------	----------

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

- [Brochures - Drive Isolation Transformers](#)
- [Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - Acme_DTGA0754S_TECHNICAL_DRAWINGS](#)
- [SDS - HCC SDS](#)
- [Specifications - DTGA0754S Specification Sheet](#)
- [Specifications - DTGA0754S Specification Sheet French](#)
- [Specifications - DTGA0754S](#)
- [Terms and Conditions - HCC Terms & Conditions](#)