



Drive Isolation Transformer - Three Phase, 460Δ - 230Y/133V, 93kVA

By Acme Electric
Catalog # [DTGA0934S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 230Y/133V, 93kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA3

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGA0934S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	230Y/133 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503089460
Winding Material	AL
kVA	93

Dimensions

Dimensions 26.88 in x 31.9 in x 35.9 in

Height	35.9 in
Length	26.88 in
Weight	685 lb
Width	31.9 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Product Assets

[Brochures - Drive Isolation Transformers](#)
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - Acme_DTGA0934S_TECHNICAL_DRAWINGS](#)
[SDS - HCC SDS](#)
[Specifications - DTGA0934S Specification Sheet](#)
[Specifications - DTGA0934S Specification Sheet French](#)
[Specifications - DTGA0934S](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand