



# Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 880kVA

By Acme Electric  
Catalog # [DTGB008804S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 880kVA.



\*Representative Image

## Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA6

## General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB008804S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000755
Winding Material	AL
kVA	880

## Dimensions

Dimensions	41.49 in x 54 in x 62.84 in
Height	62.84 in
Length	41.49 in
Weight	3816 lb

Width 54 in

## Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

## Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

## Logistics

Carton Quantity	1
Pallet Quantity	4

## Product Assets

Brochures - Drive Isolation Transformers
Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing -
<a href="#">Acme_DTGB008804S_TECHNICAL_DRAWINGS</a>
SDS - HCC SDS
Specifications - <a href="#">DTGB008804S</a>
Specifications - <a href="#">DTGB008804S Specification Sheet French</a>
Specifications - <a href="#">DTGB008804S Specification Sheet</a>
Terms and Conditions - <a href="#">HCC Terms &amp; Conditions</a>



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
ACME\_CA-DTGB008804S-SPEC-EN | REV 1/2025