



Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 145kVA

By Acme Electric
Catalog # [DTGB01454S](#)

Drive Isolation Transformer - Three Phase, 460Δ - 460Y/266V, 145kVA.



*Representative Image

Features

- Copper terminations for trouble free operation
- Wound core and strip winding for low losses
- Electrostatic shield for enhanced protection
- Full capacity taps on all units
- Optional weather shield - WSA4

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	DTGB01454S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	460Δ
Product Category	Drive Isolation Transformer
Secondary Voltage	460Y/266 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503000779
Winding Material	AL
kVA	145

Dimensions

Dimensions 29.88 in x 32.9 in x 41.52 in

Height	41.52 in
Length	29.88 in
Weight	990 lb
Width	32.9 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	460D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 1561

Product Assets

[Brochures - Drive Isolation Transformers](#)
[Catalogs - Acme Electric Catalog - Section 4 - Drive Isolation and AC Line Reactors](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - Acme_DTGB01454S_TECHNICAL_DRAWINGS](#)
[SDS - HCC SDS](#)
[Specifications - DTGB01454S](#)
[Specifications - DTGB01454S Specification Sheet French](#)
[Specifications - DTGB01454S Specification Sheet](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
ACME_CA-DTGB01454S-SPEC-EN | REV 1/2025